



PRODUCT NUMBER: LA132G Nitri Guard Plus - LA132G

Mechanical and chemical resistance to a large range of products (oils, detergents and many solvents). Preparation of greasy products, production of paints, varnishes.

Honeywell

Overview

Reference Number

LA132G

Product Type

Gloves

Range

Chemical Protection

Line

Heavy chemical

Brand

Honeywell

Brand formerly known as

NORTH

Industry

- Agriculture
- Automotive and Part Manufacturer
- Chemical Industries
- Food Industries
- Industrial Cleaning
- Laboratory
- Petro-chemical
- Water treatment

Product Use

Mechanical and chemical resistance to a large range of products (oils, detergents and many solvents). Preparation of greasy products, production of paints, varnishes.

Features & Benefits

Feature

Unsupported nitrile glove. Flocked cotton. Raised pattern. Thickness : 0.38 mm. Length : 33 cm.

Benefit

COMFORT Its nitrile formula has been selected to give the glove greater elasticity and unrivalled dexterity. The cotton flocked interior provides the user with greater comfort. The glove's rough finish improves the grip, to grasp objects in a greasy or damp atmosphere. Gloves will not swell, sag or weaken from fat absorption. Curved shaped hand provides a natural fit. **RESISTANCE** Nitrile ensures good chemical properties and excellent mechanical characteristics (abrasion). It is particularly suitable for the handling of oils, greases and hydrocarbons. Out performs natural rubber, neoprene and vinyl gloves when exposed to solvents, caustics and animal fats. Avoid contact with solvents containing ketones. **SAFETY**

Category III glove for constant quality. The cuff helps to protect a part of the forearm. HYGIENE Gloves are free of latex proteins which can cause allergic reactions

Technical Description

Description

Unsupported nitrile glove. Flocked cotton. Raised pattern. Thickness : 0.38 mm. Length : 33 cm.

Product Technology

Dipped

Glove/liner color

Green

Coating Type

Nitrile

Length

33 cm

Thickness

0,38 mm

Harmlessness

In conformity with the European standards.

Dexterity

Class 5

Sizes

7S, 8M, 9L, 10XL, 11XXL

EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	3
Cutting resistance (Coupe test)	1
Tear resistance	0
Puncture resistance	1

EN 374-3 Resistance to

Resistance to permeation by chemicals	JKL
---------------------------------------	-----

Packaging Label

Tagging

CE0075 Honeywell LA132G XX EN 420 EN 388 : 3101 EN 374-3 : JKL

Certifications

EC Category PPE

3

EC Certificate Number

0075/797/162/08/13/0760 EXT04/04/15

EC Attestation

EC Attestation

EC Attestation Number

0075/797/162/08/13/0760 EXT04/04/15

Certifications

- EN (0075/797/162/08/13/0760 EXT04/04/15)

Additional Information

User Manual

UI 104

Maintenance

Storage Information

Minimum packaging : 12 pairs. Cartons of 144 pairs.

Care Instructions

In order to keep its properties, this article should not be cleaned.